

Features:

Model: XH-W3001

Name: Temperature Controller

1. Temperature measurement, display; refrigeration, heating control
2. Temperature setting upper and lower limits
3. Simple operation, suitable for seafood machines.
4. Easy to install

Specification:

1. Measurement range: $-50^{\circ}\text{C} \sim 110^{\circ}\text{C}$
2. Control range: $-50^{\circ}\text{C} \sim 110^{\circ}\text{C}$
3. Measuring accuracy: plus or minus 0.2°C
4. Control precision: plus or minus 0.1°C
5. Measuring input: NTC10K L= 1 m waterproof probe
6. Power: 1500W
7. Input voltage: 220V
8. Current: Max 10A
9. Size: 60 * 45 * 31 mm

How to use:

1. Press the up button show the starting temperature
long press UP button the temperature display Flashing , press the UP or Down button Set the start temperature value
2. Press the Down button show the Stop temperature
long press Down button the temperature display Flashing , press the UP or Down button Set the stop temperature value

wiring method



Features:

Model: XH-W3001

Name: Temperature Controller

1. Temperature measurement, display; refrigeration, heating control
2. Temperature setting upper and lower limits
3. Simple operation, suitable for seafood machines.
4. Easy to install

Specification:

1. Measurement range: $-50^{\circ}\text{C} \sim 110^{\circ}\text{C}$
2. Control range: $-50^{\circ}\text{C} \sim 110^{\circ}\text{C}$
3. Measuring accuracy: plus or minus 0.2°C
4. Control precision: plus or minus 0.1°C
5. Measuring input: NTC10K L= 1 m waterproof probe
6. Power: 1500W
7. Input voltage: 220V
8. Current: Max 10A
9. Size: 60 * 45 * 31 mm

How to use:

1. Press the up button show the starting temperature
long press UP button the temperature display Flashing , press the UP or Down button Set the start temperature value
2. Press the Down button show the Stop temperature
long press Down button the temperature display Flashing , press the UP or Down button Set the stop temperature value

wiring method

